

MATERIAL SAFETY DATA SHEET



SC PROF DB2K BLACK

1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

Identification of the substance or mixture

Product name : SC PROF DB2K BLACK
Product code : 56380801
Chemical name : SC PROF DB2K BLACK
Synonyms : Not available.
Chemical formula : Not applicable.
CAS number : Not applicable.

Company/undertaking identification

Manufacturer : Asian Paints Ltd,
6A, Shantinagar,
Opp Hotel Grand Hyatt,
Santacruz(E), P.O. Box No. 6818,
Mumbai 400 055

Supplier : Asian Paints Ltd,
6A, Shantinagar,
Opp Hotel Grand Hyatt,
Santacruz(E), P.O. Box No. 6818,
Mumbai 400 055

e-mail address of person responsible for this SDS : customercare@asianpaints.com

Emergency telephone number (with hours of operation) : 1800-209-5678 (8 am to 8 pm (every day of the week except national holidays)
022 – 62503500 (8 pm to 8 am)

2. HAZARDS IDENTIFICATION

Risk phrases : This product is not classified according to EU legislation.

Additional hazards : None known.

See Section 11 for more detailed information on health effects and symptoms.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance/preparation : Mixture

Ingredient name	CAS number	%
barium sulfate	7727-43-7	5 - 15

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

4. FIRST AID MEASURES

Inhalation : Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if symptoms occur.

Ingestion : Wash out mouth with water. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if symptoms occur.

Skin contact : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur.

Eye contact : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Get medical attention if irritation occurs.

See Section 11 for more detailed information on health effects and symptoms.

5. FIRE-FIGHTING MEASURES

Extinguishing media

Suitable : Recommended: alcohol-resistant foam, CO₂, powders, water spray.

Not suitable : Do not use water jet.

Special exposure hazards : In a fire or if heated, a pressure increase will occur and the container may burst.
Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Hazardous thermal decomposition products : Decomposition products may include the following materials:
sulfur oxides
metal oxide/oxides

Special protective equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Put on appropriate personal protective equipment (see Section 8).

Environmental precautions : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods for cleaning up

Small spill : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill : Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor.

7. HANDLING AND STORAGE

Handling : Put on appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas.

Storage : Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure limit values

Ingredient name

barium sulfate

barium sulfate

Occupational exposure limits

ACGIH TLV (United States, 3/2012).

TWA: 10 mg/m³ 8 hours.

ACGIH TLV (United States, 3/2012).

TWA: 10 mg/m³ 8 hours.

OSHA PEL 1989 (United States, 3/1989).

TWA: 5 mg/m³ 8 hours. Form: Respirable fraction

TWA: 10 mg/m³ 8 hours. Form: Total dust

NIOSH REL (United States, 1/2013).

TWA: 5 mg/m³ 10 hours. Form: Respirable fraction

TWA: 10 mg/m³ 10 hours. Form: Total

OSHA PEL (United States, 6/2010).

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

TWA: 5 mg/m³ 8 hours. Form: Respirable fractionTWA: 15 mg/m³ 8 hours. Form: Total dust

- Recommended monitoring procedures** : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.
- Exposure controls**
- Occupational exposure controls** : No special ventilation requirements. Good general ventilation should be sufficient to control worker exposure to airborne contaminants. If this product contains ingredients with exposure limits, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.
- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
- Respiratory protection** : Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
- Hand protection** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
- Eye protection** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.
- Skin protection** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

9. PHYSICAL AND CHEMICAL PROPERTIES

- Physical state** : Liquid.
- Odor** : Not available.
- Odor threshold** : Not available.
- pH** : Not available.
- Boiling point** : Not available.
- Melting point** : Not available.
- Flash point** : Not available.
- Vapor pressure** : Not available.
- Solubility** : Not available.
- Vapor density** : Not available.
- Auto-ignition temperature** : Not available.
- Density** : 1.78 g/cm³
- Flammability** : Not available.

10. STABILITY AND REACTIVITY

Chemical stability	: The product is stable.
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.
Conditions to avoid	: No specific data.
Materials to avoid	: No known incompatibility

11. TOXICOLOGICAL INFORMATION

Potential acute health effects

Inhalation	: No known significant effects or critical hazards.
Ingestion	: No known significant effects or critical hazards.
Skin contact	: No known significant effects or critical hazards.
Eye contact	: No known significant effects or critical hazards.

Potential chronic health effects

Chronic effects	: No known significant effects or critical hazards.
Carcinogenicity	: No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Teratogenicity	: No known significant effects or critical hazards.
Developmental effects	: No known significant effects or critical hazards.
Fertility effects	: No known significant effects or critical hazards.
Denmark Carcinogen list	: Contains a substance or substances listed under National Working Environment Authorities Executive Order 908/2005.

Over-exposure signs/symptoms

Inhalation	: No specific data.
Ingestion	: No specific data.
Skin	: No specific data.
Eyes	: No specific data.

12. ECOLOGICAL INFORMATION

Ecotoxicity	: No known significant effects or critical hazards.
-------------	---

Aquatic ecotoxicity

Product/ingredient name	Test	Result	Species	Exposure
barium sulfate	-	Acute EC50 634 mg/l Fresh water	Crustaceans - Ostracod - Cypris subglobosa	48 hours
	-	Acute EC50 32000 µg/l Fresh water	Daphnia - Water flea - Daphnia magna	48 hours

Conclusion/Summary	: Not available.
--------------------	------------------

Other adverse effects	: No known significant effects or critical hazards.
-----------------------	---

13. DISPOSAL CONSIDERATIONS

Methods of disposal	: The generation of waste should be avoided or minimized wherever possible. Waste product residues should not be disposed of via the sewer but processed in a suitable effluent treatment plant. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.
---------------------	---

14. TRANSPORT INFORMATION

International transport regulations

Regulatory information	UN number	Proper shipping name	Classes	PG*	Label	Additional information
ADR/RID Class	Not available.	Not available.	Not available.	-		-
ADN/ADNR Class	Not available.	Not available.	Not available.	-		-
IMDG Class	Not available.	Not available.	Not available.	-		-
IATA Class	Not available.	Not available.	Not available.	-		-

PG* : Packing group

15. REGULATORY INFORMATION

Risk phrases

: This product is not classified according to EU legislation.

Product use

: Consumer applications.

16. OTHER INFORMATION

National Fire Protection Association (U.S.A.)

:



History

Date of printing

: 05-06-2017.

Date of issue/ Date of revision

: 05-06-2017.

Date of previous issue

: 02-06-2017.

Version

: 0.04

Indicates information that has changed from previously issued version.

Disclaimer

Information contained in this material safety data sheet is believed to be reliable and given in good faith, but no representation, guarantee or warranties of any kind are made as to its accuracy, suitability for a particular application or results to be obtained from them.

The user of this material decides what safety measures are necessary to safely use this material, either alone or in combination with other materials.

Asian Paints Limited makes no warranties expressed or implied in respect of the adequacy of this document for any particular purpose.

SC PROF DB2K BLACK