

PRODUCT DATA SHEET

January, 2022

DESCRIPTION

VALUEPRO PE PUTTY CREAM (V1110031)

PRINCIPAL CHARACTERISTICS

- Easy to mix and smooth,
- It offers excellent hold out with quick drying ,
- Easy clog-free sanding properties and
- Suitable for filling deep and shallow indentation.

BASIC DATA AT 30°C

Viscosity on Penetrometer	275-285 DOP
Mixing ratio with hardener	100:2-3 by weight
Pot life	2 – 5 minutes
Hard dry	10-20 minutes
Sanding	Sanding activity should be done after hard drying of the film
Application	For deep filling it is best to apply in several thick layers. Allow each layer to dry between applications.
Shelf life	6 MONTHS

RECOMMENDED SUBSTRATES AND PREPARATION

- Bare steel, aluminium, GI, FRP or fully cured enamels.
- If the original finish is thermoplastic acrylic or cellulose based apply only to bare metal.
- For substrate preparation, de-rust and degrease bare metal and existing finishes. Scuff with P80-P120 sandpaper.
- Clean thoroughly with Spirit Wipe

STORAGE AND HANDLING

Storage conditions are to keep the containers in a dry and well ventilated space and away from source of heat and ignition. Containers must be kept tightly closed. Handle with care. Stir well before use.

HEALTH AND SAFETY

For detailed information on the health and safety hazards and precautions for use of this product, please refer to the Material Safety Data Sheet (MSDS).

DISCLAIMER

The information in this data sheet is given to the best of our knowledge based on laboratory testing and practical experience. However, as the product can be used under conditions beyond our control.

We also reserve the right to change the given data without notice. Minor product variations may be implemented in order to comply with local requirements.