

Zaffiano

Drawing inspiration from the subtle elegance of leather, Zaffiano brings interiors to life with a soft, rich texture that beautifully stands out in different lights and colour. This interior decorative finish creates a deep, chromatic depth-inviting touch and visual intrigue

PRODUCT FEATURES

AVAILABLE PACKS

Available in 1 kg.

The packaged product is guaranteed for 24 months, if stored in the original sealed packages and at the adequate temperatures.

COLOUR

12 shades

RECOMMENDED USAGE

Due to the balanced formulation and the use of proper inerts and additives, Zaffiano is highly recommended for

- a) New renderings or old plasters
- b) Concrete surfaces
- c) Old paints or dry, compact, absorbent, mineral coatings
- d) Various absorbent mineral substrates
- e) Insulating systems
- f) Plasterboards

WASHABILITY

Zaffiano applied surfaces are low washable & stain resistant.

Other

VOC - Contains 200g/l of VOC maximum.

Flash point - NA

HOW TO APPLY

PRODUCT PREPARATION & APPLICATION

Zaffiano Direction for use

Base Preparation - Cleaning: Sand the surface with emery paper 180. Wipe clean. **Primer:** Apply a coat of Asian Paints wall primer (DCP WT). Allow drying for 3-4 hrs. **Acrylic Putty:** Smoothen the Surface with Asian Paints Acrylic Putty. Apply two to three coats to

make the wall smooth. Allow proper drying in between two coats.

Primer: Sand with emery paper 180 & wipe clean. Apply a coat of Asian Paints Wall primer (DCP WT).

Allow drying for 3-4 hrs.

Application of 1 coat of Apcolite Premium

Emulsion - Apply a Coat of Tinted Premium Emulsion with application roller. Only use the correct shade combination of Premium Emulsion given in the shade card.

Zaffiano Base Coat Application – Apply 1st coat of Zaffiano Base Coat on the primed surface using a steel trowel. Allow it to dry for 6-8hrs. Apply 2nd coat of Zaffiano base coat & create Pattern using the trowel. . Allow it to dry for 6-8 hrs.

Zaffiano Top Coat Application – After 6 to 8 hrs of complete drying, apply the 1st coat of Royale Play Zaffiano Top Coat. (max dilution 1%).

YIELD

Zaffiano Base Coat - 50-60 sqft for 2 coats
Zaffiano Top Coat - 80-100 sqft for 1 coat

TOOLS

Clean with water, immediately after use.

DILUTION

Zaffiano Base Coat - Ready to use
Zaffiano Top Coat - 1% with water

ADDITIONAL INFORMATION

SAFETY FEATURES

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment / Keep out of the reach of children / Do not empty into drains
Wear suitable protective clothing and gloves / If swallowed, seek medical advice immediately and show container or label.

The product must be transported, used and stored in accordance with the standards in force regarding hygiene and safety; let the residues dry out completely and treat them as special waste. For more information see the safety data sheet. The information herein is provided to the best of its technical and scientific knowledge and based on its experience.

Nonetheless, the company may not be held liable for the results obtained using these products, as application conditions are beyond its control. It is recommended to always make sure that the product is suited to each specific instance. The present sheet voids and replaces any previously existing sheets.

RECOMMENDATIONS

During the entire application process, the product must be protected from cold and high heat changes. Do not apply with air, substrate and product temperature lower than +5°C and higher than +35°C, nor under direct sun light, nor on superheated surfaces (even if already in shadow). Environmental humidity must be <75%; substrate humidity must be <10%. It is advisable to complete each work with materials from the same batch of production. When using multiple batches, it is recommended to remix the various products

together to avoid slight differences in shading. For the application of specific tints of Intosil Fine on insulation systems, it is recommended to check first the feasibility of the tint. For the correct use, dilution and application of the products here mentioned, consult their respective technical data sheets. During the preparation of the substrate and application of the products, it is recommended the correct use of tools and individual protective devices (dpi).

WARNING

Properly mix the product before tinting and application. Do not apply on fresh/new substrates; wait a maturation period, generally of 4 weeks.