

PRODUCT CODE 5608

Wall 2 Floor Athena

Wall 2 Floor Athena is a base coat which grants a perfect link with the surface that must be covered with Wall 2 Floor Rasal, creating in this way a suitable surface for the application of the "Wall 2 Floor System". It is made up of acrylic water-based polymers and selected additives which gives to the product an excellent adherence on smooth surfaces such as tiles, mosaics, etc.



PRODUCT FEATURES

AVAILABLE PACKS

Available in 5 L pack
The packaged product is guaranteed for 24 months, if stored in the original sealed packages and at the adequate temperatures between +10°C and +30°C.

IDENTIFICATION

Density: 1.40 +/- 0.05 g/l
Viscosity (packaging): 7800 +/- 500 cps at 25°C
Drying process (at 25°C and 65% of humidity): to the touch 1 hour; it can be painted over after at least 8 hours, and no later than 48 hours.

RECOMMENDED USAGE

Wall 2 Floor Athena is recommended for usage on:

1. Tiles
2. Mosaics

COLOUR

White

HOW TO APPLY

PRODUCT PREPARATION & APPLICATION

Before application, ensure that the surface is dry & clean. Apply 1st coat of Wall 2 Floor Athena primer with roller. Allow it to dry for 6 hours. Apply 2nd coat with roller and allow to dry for 6 hours.

YIELD

Forced coverage of 5-6 m²/l for two coats, depending on the kind of substrate.

TOOLS

Clean with water immediately after their use

DILUTION

The product is ready for use. Maximum dilution: 10%. Shake the product before the use.

ADDITIONAL INFORMATION

SAFETY FEATURES

- > EU Directive 2004/42/CE:
- > Cat. I: mono-component paints with high performances (water based): 140 g/l (2010).
- > Wall 2 Floor Athena contains maximum 140 g/l of COV.
- > Do not empty into drains, water courses or onto the ground; after use do not litter containers, allow the residue to dry and treat them as special waste. Keep out from children presence. If swallowed, seek medical advice immediately and show this container or label. For more information, see the safety data sheet.
- > The information herein is provided to the best of technical and scientific knowledge and based on experience; nonetheless, the company may not be held liable for the results obtained using these products, as application conditions are beyond its control. It is recommended to always make sure that the product is suited to each specific instance. The present sheet voids and replaces any previously existing sheets

RECOMMENDATIONS

Keep the product protected from intense cold and from sudden changes of temperatures during the application cycle. Do not apply with air temperature lower than +5°C and higher than +35° C. or under direct sunlight or on hot surfaces (even if already in shadow). If stored to as temperature close to +5°C, it is suggested to keep the product in an area with a temperature not lower than 10°C. Do not heat the products using a direct source of heat, flame, hot body or similar. Low temperatures increase the viscosity in the bucket making it difficult to use and extend or inhibit the drying and hardening process of the various products.

Maximum storage temperature: +30° C Minimum storage temperature: +10° C If possible, use the same batch of production. If different batches of production are used, it is recommended to mix them in order to avoid slight different shades. For the correct use, dilution and application of the products here mentioned, consult their respective technical data sheets. During the preparation of the substrate and application of the products, it is recommended the correct use of tools and individual protective devices (dpi).