

Product Code 6A41

Stucco Mirror

Stucco Mirror is slaked lime coating from the Italian tradition, its natural and ecological and gives you the high gloss marble effect. The application of Stucco Mirror makes it possible to create high quality, glossy effect decorations in vibrant tones, with a touch of heritage that reminds on the great buildings of the past.



PRODUCT FEATURES

AVAILABLE PACKS

Available in 1 Kg & 5 Kg Packs



Product Shelf life is 2 years from date of manufacture in original tightly closed containers away from direct sunlight and excessive heat.

COLOUR

Refer Stucco Mirror Shade Chart

RECOMMENDED USAGE

Recommended on:

- a) New renderings or old plasters
- b) Concrete surfaces
- c) Old paints or dry, compact, absorbent, mineral coatings
- d) Various absorbent mineral substrates
- e) Insulating systems
- f) Plasterboards
- h) Marine mdf

WASHABILITY

As it's a lime based plaster, stains or dirt that accumulates on the wall can be wiped with a dry cloth. Provides medium Washability

HOW TO APPLY

PRODUCT PREPARATION & APPLICATION

Base Preparation - Cleaning: Sand the surface with emery paper 180. Wipe clean. Primer: Apply a coat of Asian Paints wall primer (DCP WT). Allow drying for 3-4 hrs. Acrylic Putty: Smoothen the Surface with Asian Paints Acrylic Putty. Apply two to three coats to make the wall smooth. Allow proper drying in between two coats. Primer: Sand

with emery paper 180 & wipe clean. Apply a coat of Asian Paints Wall primer (DCP WT). Allow drying for 3-4 hrs.

Application of Stucco Mirror - Apply 1st coat of Royale Play stucco mirror plain and buff with the help of Trowel & Scraper. Allow it to dry for 4 to 6 hrs. After drying, sand the surface using 220 grade sanding paper. Apply

2nd coat of Stucco Mirror with trowel & scraper & create pattern as per catalogue or customisation and buff manually in the direction of the pattern. Allow it to dry for 4 to 6 hrs.

Final buffing - Buffing using sanding machine with sanding paper grade 3000 & 4000.

YIELD

18-20 sqft per kg, in two layers, depending on the kind of substrate and its absorption rate.

TOOLS CLEANING

Clean with water, immediately after use.

DILUTION

Ready to use.

ADDITIONAL INFORMATION

SAFETY FEATURES

Store the container with the lid tightly closed in an upright position, in a cool, dry place. Keep out of reach of children and away from eatables. May be harmful if swallowed. In case of ingestion seek immediate medical attention. Wear eye protection during application. In case of contact

with eyes, rinse immediately with plenty of water and seek medical advice. In case of skin contact immediately wash skin with soap and plenty of water. Get medical attention if irritation develops or persists. Do not breathe vapour or spray. It is recommended to wear suitable nose pad during

sanding and surface preparation to avoid dust inhalation. Do not pour leftover paint down the drain or in water courses. In the event of spills, contain spillage using sand or earth. No added Lead, Mercury or Chromium compounds.

RECOMMENDATIONS

Store the container with the lid tightly closed in an upright position, in a cool, dry place. Keep out of reach of children and away from eatables. May be harmful if swallowed. In case of ingestion seek immediate medical attention. Wear eye protection during application. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. In case of skin contact immediately wash skin with soap and plenty of water. Get medi-

cal attention if irritation develops or persists. Do not breathe vapour or spray. It is recommended to wear suitable nose pad during sanding and surface preparation to avoid dust inhalation. Do not pour leftover paint down the drain or in water courses. In the event of spills, contain spillage using sand or earth. No added Lead, Mercury or Chromium compounds.

WARNING

Properly mix the product before the application. Do not apply on fresh surfaces, wait for the adequate maturation time, generally of 4 weeks. Application on concrete surfaces has a decorative function. Do not apply in the presence of rising damp. For removing stains, wipe clean with a dry cloth. Ensure a drying time of at least 2 weeks before cleaning.