



Product Description

Utsav Metal Primer is a Red Oxide primer that can be used as an undercoat for ferrous metal substrates.

Performance Features & Benefits

Utsav Metal Primer has good anti-settling properties and offers good opacity, coverage, and flow and leveling.

Recommended Usage

Utsav Metal Primer – Red Oxide is suitable for priming ferrous metal substrates.

Recommended Application

Prepare the surface to be painted by sanding it with Emery Paper 180. Wipe the surface clean.

Apply coating as follows :

Product	Product Code	Thinner	Dilution % (by vol)	Application Viscosity (sec)	Recoating Period (hrs)
Asian Paints Utsav Metal Primer – Red Oxide 1st coat Brushing	0080	MTO	 4-5%	 40-45	6-8 hrs
Sand lightly with Emery Paper 180 and wipe clean					
AKPF – Grey (Optional) Smoothen the surface by filling dents with thin coats of Asian Paints Knifing Paste Filler. Allow it to dry for 4 - 6 hours. Sand lightly with Emery Paper 180 and wipe clean.					
Asian Paints Utsav Metal Primer – Red Oxide 2nd coat Brushing on areas where KPF is applied	0080	MTO	 4-5%	 40-45	6-8 hrs
Sand lightly with Emery Paper 320 before application of topcoats.					

*Recoat times are quoted for 25°C and 50% Relative Humidity, these may vary under different conditions.

 Brush

Technical Data

- a) Coverage:** One coat 14-16 sq. mtrs/ltr/coat at 25 micron DFT depending on surface and surface preparation.
- b) Drying Time:** 6-8 hours.
- c) Gloss Levels/Sheen Levels:** Matt.
- d) Flash Point (IS 101/1987, Part 1, Sec 6):**
- e) Shelf-life:** 1 1/2 year in original tightly closed containers away from direct sunlight and excessive heat.

Precautions

- a) Store the product at ambient conditions in well ventilated locations and away from source of ignition and fire.
- b) Avoid eye and skin contact. In case of eye and skin contact wash with plenty of clean water.
- c) Do not inhale or inject. In case of inhalation move to fresh air. Seek medical attention if symptoms persist in both the cases.
- d) Use protective equipments like rubber/polythene gloves, safety goggles/glasses and face mask while handling the paint.

Post Application Instructions

NA

Safety Features

Pack Sizes & Shade Range

Pack size availability:
500 ml, 1 ltr, 4 ltr, 20 ltr

Shade Range:
Red Oxide

Contact us

For more information, visit our website at www.asianpaints.com
For feedback /complaints, write to Marketing Manager - Services, or call **1800-209-5678** (service available in select cities only)
Please note that this data sheet supersedes any previous versions.

